


1. SPECIFICATION


AR-120632-PM-1P

	ITEM	UNIT	SPECIFICATIONS	CONDITION
01	Dimension 尺寸	mm	Φ 12 X 6	Refer to attached drawing in details.
02	Input power 輸入功率	mW	20	White noise is applied for 96 hours.
03	Max. Input power 額定輸入最大功率	mW	Max. 30	at room temperature for 60s on and 120s off for 10 cycles.
04	Impedance 交流阻抗	Ω	32 ±15%	at 1KHz /1V.
05	S.P.L 音壓位準 Sound pressure level	dB	113 ±3	at 1KHz 179mV /1mW with IEC318 coupler.
06	Frequency range 有效頻寬	Hz	300~3.4K	
07	T.H.D 總諧波失真 Total Harmonics Distortion	%	Max. 10	at 1KHz 179mV / Input power.

REV NO.	REVISION NOTE	APPROVAL	DATE
---------	---------------	----------	------



Recommended pad layout



RoHS

TITLE: <i>DYNAMIC RECEIVER</i>		DRAWN: Zack 2018/11/05	SCALE: 2:1	SHEET: 1:1
PART NO. <i>AR-120632-PM-1P</i>		DESIGNED: R&D OF AAT	UNITS: mm	
DWG NO. <i>UGRP120632-19T-11</i>		CHECKED:	TOLERANCE ± 0.5	
REV 2		APPROVAL:	UNLESS OTHERWISE SPECIFIED:	
		MATERIAL: PPA	ONE PLACE DECIMAL ± ***	
			TWO PLACE DECIMAL ± ***	
			THREE PLACE DECIMAL ± ***	



ADVANCED ACOUSTIC TECHNOLOGY CORPORATION

For more information, please contact AATC.

AATC