

1. SPECIFICATIONS

AMB-O60G42-6CWH


01	Electret's Type	Back type
02	Sensitivity	-42±3dB (0dB=1V/Pa,1KHz)
03	Standard Operation Voltage	2.0 V
04	Output Impedance	2.2 KΩ
05	Directivity	Omni directional
06	Frequency Range	100 - 20K Hz
07	Max. Operation Voltage	10V
08	Current Consumption	Max.0.5mA
09	Sensitivity Reduction	Within -3dB 0dB=1V/Pa,1KHz Vs=2.0to 1.5V
10	S/N Ratio	≥58dB
11	Sound Pressure Level	110 dB

REV NO.

REVISION NOTE

APPROVAL

DATE



WIRE: UL1571, AWG32#
Holder: DD-EQ-JTC70-14

RoHS

TITLE: <i>MICROPHONE</i>		DRAWN: <i>Moose</i> 2017/05/18	SCALE: 5:1	SHEET: 1 of 1
PART NO. <i>AMB-060G42-6CWH</i>	1	DESIGNED: R & D OF AAT	UNITS: mm	
DWG NO. <i>B6022AL-SDN-28-M 11770</i>		CHECKED:	TOLERANCE ± 0.3	
		APPROVAL:	UNLESS OTHERWISE SPECIFIED:	
	REV	MATERIAL: AL	ONE PLACE DECIMAL $\pm$ ***	
			TWO PLACE DECIMAL $\pm$ ***	
			THREE PLACE DECIMAL $\pm$ ***	



ADVANCED ACOUSTIC TECHNOLOGY CORPORATION

For more information, please contact AATC.

AATC