

1. SPECIFICATION

AKR-535308100-MU-1C2

ITEM		SPECIFICATIONS	
01	Type	Dynamic speaker	
02	Dimension	External diameter 53 x 53 mm	
03	Rated Input Power	10 W	
04	Max. Input Power	15 W for 1 minute	
05	Impedance	$8\Omega \pm 15\%$ at 1KHz 1V	
06	Resonance Frequency (Fo)	200 Hz $\pm$ 20% at Fo, 1V	
07	Sound pressure level	121 dB(10W/0.1M) $\pm$ 3 dB	at AVE 0.4 0.5, 0.6, 0.8 KHz.
08	Frequency Range	Fo – 10 K Hz	
09	Total Harmonics Distortion	Max 10 % at 1 KHz, 1.0W.	
10	Magnet	Rare earth permanent (NdFeB) magnet Φ 18X5 mm	
11	Weight	69g $\pm$ 20g	
12	Appearance	Should not exist any obstacle to be harmful to normal operation; damages, cracks, rusts and distortions, etc.	
13	Operation Test	Must be normal at program source 10 W	
14	Buzz, Rattle, etc.	Should not be audible at 8.9 V sine wave between Fo to 2KHz	
15	Polarity	When positive voltage is applied to the terminal marked (+), diaphragm should move to the front.	
16	Terminal Strength	Capable of withstand 1kg load for 15 seconds without resulting in any damage or rejection.	
17	Temperature	Operating temperature: -20°C to +60°C Storage temperature: -30°C to +70°C	

3. DIMENSIONS

