


1. SPECIFICATION

AKR2-18160420-PM1C

ITEM		SPECIFICATIONS	
01	Type	Dynamic speaker	
02	Dimension	External diameter 18 x 16 mm	
03	Rated Input Power	2.0 W in 1cc box	
04	Max. Input Power	2.2 W for 1 minute in 1cc box	
05	Impedance	$4\Omega \pm 15\%$ at 2 KHz 1V	
06	Resonance Frequency (Fo)	1050 Hz $\pm$ 20% at Fo, 1V in 1cc box	
07	Sound pressure level	103 dB(2.0W/0.1M) $\pm$ 3 Db in 1cc box	at AVG 1.0, 1.2, 1.4, 1.5 KHz.
08	Frequency Range	Fo – 20 K Hz	
09	Total Harmonics Distortion	Max 10 % at 1 KHz, 1.0 W.	
10	Magnet	Rare earth permanent (NdFeB)	
11	Weight	7.9 g $\pm$ 0.3 g	
12	Appearance	Should not exist any obstacle to be harmful to normal operation; damages, cracks, rusts and distortions, etc.	
13	Operation Test	Must be normal at program source 2.0W	
14	Buzz, Rattle, etc.	Should not be audible at 2.83 V sine wave between Fo to 2KHz	
15	Polarity	When positive voltage is applied to the terminal marked (+), diaphragm should move to the front.	
16	Terminal Strength	Capable of withstand 1kg load for 15 seconds without resulting in any damage or rejection.	
17	Temperature	Operating temperature: -20°C to +60°C Storage temperature: -20°C to +70°C	

2. DIMENSIONS



For more information, please contact AATC.

AATC