

1. SPECIFICATION

AK-570830-MMW1C

ITEM		SPECIFICATIONS	
01	Type	Dynamic speaker	
02	Dimension	External diameter 50 mm	
03	Rated Input Power	3.0 W	
04	Max. Input Power	5.0 W for 1 minute	
05	Impedance	8Ω± 15% at 1 KHz 1V	
06	Resonance Frequency (Fo)	600 Hz ± 20% at Fo, 1V	
07	Sound pressure level	88 dB(1.0W/0.5M) ± 3 dB	at AVG 0.8, 1.0, 1.2, 1.5 KHz.
		105 dB(3.0W/0.1M) ± 3 dB	
08	Frequency Range	Fo – 5.0 K Hz	
09	Total Harmonics Distortion	Max 10 % at 1 KHz, 1.0 W.	
10	Magnet	Rare earth permanent (NdFeB)	
11	Weight	29 g ± 3 g	
12	Appearance	Should not exist any obstacle to be harmful to normal operation; damages, cracks, rusts and distortions, etc.	
13	Operation Test	Must be normal at program source 3.0 W	
14	Buzz, Rattle, etc.	Should not be audible at 4.89 V sine wave between Fo to 2KHz	
15	Polarity	When positive voltage is applied to the terminal marked (+), diaphragm should move to the front.	
16	Terminal Strength	Capable of withstand 1kg load for 15 seconds without resulting in any damage or rejection.	
17	Temperature	Operating temperature: -40℃ to +85℃ Storage temperature: -40℃ to +85℃	
18	Waterproof	IPX7(For diaphragm protection only)	

3. DIMENSIONS

