

1. SPECIFICATIONS

AMF-097L42-1CWH1

01	Sensitivity	-42±3dB (0dB=1V/Pa,1KHz)
02	Standard Operation Voltage	1.5 V
03	Output Impedance	1.5KΩ
04	Directivity	Omni directional
05	Frequency Range	100 - 10K Hz
06	Max. Operation Voltage	10V
07	Current Consumption	Max.0.5mA
08	Sensitivity Reduction	Within -3dB 0dB=1V/Pa,1KHz Vs=2.0to 1.5V
09	S/N Ratio	≥58dB
10	Sound Pressure Level	110 dB
11	Operating Temperature	-20~+60°C
12	Storage Temperature	-25~+70°C

※ For noise-cancelling use, please refer to unidirectional or bidirectional types.

2. MEASURING METHOD

2-1. Test Condition

Standard Conditions:

Generally Temperature 15~35°C

Generally Humidity 45~85%

Generally Atmospheric Pressure 860~1060hpa

Basic Test Conditions:


Temperature 20±2°C

Humidity 60~70%

Generally Atmospheric Pressure 860~1060hpa

2-2. Standard Test Circuit

Vs=1.5V RL=1.5KΩ Te=20°C R.H.=60%



3. DIMENSIONS

