


1. SPECIFICATION

AZ-P17N40

| ITEM | | UNITS | SPECIFICATIONS | CONDITIONS |
|------|---|----------------|----------------|--|
| 01 | Operating Voltage | V | 1 ~ 30 |  Square wave 1/2 duty. |
| 02 | Rated Voltage | V | 9 | |
| 03 | Rated Frequency | Hz | 4000 | |
| 04 | Consumption Current | mA (Max) | 5 | Rated voltage, Rated frequency. |
| 05 | Sound pressure level (Distance at 10cm) | dB(A) (Min) | 85 | |
| 06 | Capacitance | pF | 15000±30% | At 1000Hz |
| 07 | Operating Temp. | °C | -20 ~ +70 | |
| 08 | Storage Temp. | °C | -30 ~ +80 | |
| 09 | Weight | g | 1.2 | |
| 10 | Housing Material | | PBT | |

2. MEASURING METHOD

2-1. Test Condition

STANDARD

Temperature : 15 ~ 35°C

Relative humidity: 45% ~ 85%,

Atmospheric pressure: 860mbar to 1060mbar.

JUDGEMENT

Temperature : 20±3°C

Relative humidity: 60% ~ 70%,

Atmospheric pressure: 860mbar to 1060mbar

3. DIMENSIONS

